


COHO CREEK CROSSING SITE 5 CULVERT REMOVAL
CROSS SECTIONAL VIEW CULVERT OUTLET



COHO CREEK SITE 5 CULVERT REMOVAL
PLAN VIEW

EXHIBIT A




EXHIBIT A

SITE 7 CULVERT REMOVAL











EXHIBIT A

SITE 8 CULVERT REPLACEMENT




SITE 8 PLAN VIEW
CULVERT REPLACEMENT



EXHIBIT A



SITE APPROACH ROADBED STABILIZATION




SITE ACCESS ROAD




NOTE: COIR ROLL INSTALLATION REQUIRES THE PLACEMENT + SECURE STAKING OF THE ROLL IN A TRENCH 3-5" DEEP, DUG ON CONTOUR. RUNOFF MUST NOT BE ALLOWED TO RUN UNDER OR AROUND ROLLS


- NOT TO SCALE -




NOT TO SCALE




LONGITUDINAL ANCHOR TRENCH




TERMINAL SLOPE AND CHANNEL ANCHOR TRENCH



ISOMETRIC VIEW



INITIAL CHANNEL ANCHOR TRENCH



INTERMITTENT CHECK SLOT

Source: Clackamas County 2009
Erosion Prevention Planning and
Design Manual

- Notes:
1. Check slots to be constructed per manufacturers specifications.
 2. Staking or stapling layout per manufacturers specifications.

**Figure II-4.1.3
Channel Installation**

Revised June 2015



**DEPARTMENT OF
ECOLOGY**
State of Washington

Please see <http://www.ecy.wa.gov/copyright.html> for copyright notice including permissions, limitation of liability, and disclaimer.

Typical Pump Bypass




Figure 3. Typical bypass pump.